

Double Foot IMPULSE SEALERS

FEATURES

- Ideal for sealing thicker materials
- Single or double sealing switch selector
- Plug-in electronic timer for variable control
- All metal construction
- Heavy duty
- No warm-up time
- Sits on rectangular base for stability

WN-Series Double Impulse Foot Sealers are ideal for sealing thicker materials. Available in 12", 18", and 24" lengths with a 5mm seal, the WN-Series foot sealers are capable of sealing materials up to 20mil total thickness. Equipped with a single and double sealing selector switch provides this sealer with the flexibility of sealing various types materials. Depending on the thickness of the material, the user has the choice of 1 or 2 elements for top and bottom heating.

Sealers are equipped with a steel frame for added safety and stability. A height adjustable working plate is also included. The manufacturer's replacement kit includes two elements. A taller stand and tension rod is also available, adding 10" in height. Working height is 30 1/4" but the extended standing tube provides a 42 1/2" working height.

Easy to Operate: Set the timer. Insert the bag between the two sealing bars and press down on the foot board. Hold down the foot board for an additional 2-3 seconds after the timer light goes off to set the seal.



	W-300T	W-450T	W-600T
Power	110V	110V	110V
Watts	1000W	1900W	2800W
Seal Length	11.8"	17.6"	23.4"
Seal Width	5mm	5mm	5mm
Standing Height	33 1/2"	33 1/2"	33 1/2"
Tray Dimensions	12" x 6"	12" x 6"	12" x 6"
Tray Adjustment Height	Up to 6.5"	Up to 6.5"	Up to 6.5"
Throat Depth	1 1/2"	1 1/2"	1 1/2"
Dimensions	13" x 14" x 34"	21" x 14" x 34"	26 1/2" x 14" x 34"
Weight	34, 28	44, 28	47, 28